




## Safe use of powered hand belt sanders

- Wear proper eye and hearing protection, and when required, respiratory protection.
- Disconnect the power supply before changing the sanding belt, making adjustments, or emptying the dust collector.
- Use sanding belts that are the same width as the pulley drum.
- Make sure the sanding belt is installed in the direction indicated on the belt and sander.
- Inspect the sanding belt before using them. Replace worn or frayed belts.
- Keep hands away from the sanding belt. Use both hands to operate the sander—one on the trigger switch, and the other on the front knob handle.
- Keep all cords clear of the sanding area during operation.
- Clean dust from the motor and vents at regular intervals.
- Do not exert excessive pressure upon the moving sander.
- Do not use a sander without an exhaust system or dust collector. Empty the collector when  $\frac{1}{4}$  full.
- Do not work on unsecured material that can be thrown by belt motion. Secure the material or use a stop block.



Project: \_\_\_\_\_ Address: \_\_\_\_\_

Employer: \_\_\_\_\_ Supervisor: \_\_\_\_\_

Date: \_\_\_\_\_ Time: \_\_\_\_\_ Shift: \_\_\_\_\_

Number in crew: \_\_\_\_\_ Number attending: \_\_\_\_\_

Other safety issues or suggestions made by crew members:

---

---

---

---

---

---

Record of those attending:

Name: (please print)	Signature:	Company:
1.		
2.		
3.		
4.		
5.		
6.		
7.		
8.		
9.		
10.		
11.		
12.		
13.		
14.		
15.		

Manager's remarks: \_\_\_\_\_

---

Manager: \_\_\_\_\_ Supervisor: \_\_\_\_\_

*(signature)*

*(signature)*



WORKING TO MAKE A DIFFERENCE  
worksafebc.com